



**CARFLEX[®] NONMETALLIC
FITTINGS**

**CARFLEX[®] LIQUIDTIGHT
FLEXIBLE NONMETALLIC
CONDUIT**

CARFLEX[®] KIT

CARFLEX[®] PRE-WIRED WHIPS

FEATURES:

- ***NONCONDUCTIVE***
- ***EASY TO INSTALL***
- ***TOTALLY NONMETALLIC
SYSTEM***
- ***NO JAGGED EDGES***
- ***STRONG YET LIGHTWEIGHT***
- ***SMOOTH INTERIOR
FACILITATES WIRE PULLING***
- ***EXCELLENT CHEMICAL
RESISTANCE***
- ***EXCELLENT OIL RESISTANCE***

1. LHP reserves the right to round orders to the nearest package quantity.

2. Prices subject to change without notice.

3. Shaded items indicate non-stock factory make-to-order items only – material is non-returnable and non-cancellable.

Carflex® Liquidtight Fittings

For Use with Carflex® Conduit. Unique one piece body design. No compression nut needed. No disassembly of components for installation. Temperature resistance up to 140°F.

90° Fittings – One Piece



Part #	Product Size	UPC Code	Carton Quantity	Carton Dimensions (L x W x H)	Case Weight (Lbs)	Case Cube (Cu. Ft.)
LN20DA-CTN	1/2"	0 34481 04395 9	20	12" x 3" x 6"	1.20	0.12
LN20EA-CTN	3/4"	0 34481 04396 6	15	12" x 3" x 6"	1.17	0.12
LN20FA-CAR	1"	0 34481 04397 3	10	6" x 4" x 6"	1.29	0.08

Assembled: Locknut, o-rings and foam washer assembled onto fitting.

Straight Fittings – One Piece



Part #	Product Size	UPC Code	Carton Quantity	Carton Dimensions (L x W x H)	Case Weight (Lbs)	Case Cube (Cu. Ft.)
LN43DA-CTN	1/2"	0 34481 04392 8	30	6" x 4" x 6"	0.78	0.08
LN43EA-CTN	3/4"	0 34481 04393 5	20	6" x 4" x 6"	1.10	0.08
LN43FA-CAR	1"	0 34481 04394 2	15	6" x 4" x 6"	1.10	0.08

Assembled: Locknut, o-rings and foam washer assembled onto fitting.

Straight Fittings – Two Piece - Nylon



Part #	Product Size	UPC Code	Carton Quantity	Carton Dimensions (L x W x H)	Case Weight (Lbs)	Case Cube (Cu. Ft.)
LT43C-CAR	3/8"	0 34481 13193 9	15	6" x 4" x 6"	1.20	0.08
LT43DU	1/2"	0 34481 08550 8	50	11.5" x 7.62" x 5.37"	4.25	0.27
LT43EU	3/4"	0 34481 08555 3	50	11.5" x 7.62" x 11.25"	6.70	0.57
LT43FU	1"	0 34481 08560 7	25	11.5" x 7.6" x 5.3"	3.80	0.27
LT43GU	1-1/4"	0 34481 08565 2	5	7.87" x 6.5" x 5.62"	1.47	0.16
LT43HU	1-1/2"	0 34481 08570 6	5	11.5" x 7.6" x 5.3"	1.80	0.26
LT43JU	2"	0 34481 08575 1	5	11.62" x 7.75" x 5.75"	2.47	0.29

90° Fittings – Two Piece - Nylon



Part #	Product Size	UPC Code	Carton Quantity	Carton Dimensions (L x W x H)	Case Weight (Lbs)	Case Cube (Cu. Ft.)
LT20C-CAR	3/8"	0 34481 13188 5	15	6" x 4" x 6"	1.60	0.08
LT20DU	1/2"	0 34481 13189 2	20	12" x 4" x 6"	2.20	0.17
LT20EU	3/4"	0 34481 13190 8	15	12" x 4" x 6"	2.50	0.17
LT20FU	1"	0 34481 08510 2	25	12" x 8" x 6"	6.89	0.33
LT20GU	1-1/4"	0 34481 08515 7	5	7.8" x 6.5" x 5.6"	1.88	0.16
LT20HU	1-1/2"	0 34481 08520 1	5	7.8" x 6.5" x 5.6"	2.35	0.16
LT20JU	2"	0 34481 08525 6	5	11.6" x 7.7" x 5.7"	3.36	0.29

Carflex® Liquidtight Flexible Nonmetallic Conduit



Part #	Product Size	UPC Code	Coil Length (Ft.)	Package Dimensions (L x W x H)	Case Weight (Lbs)	Case Cube (Cu. Ft.)
15004-100	3/8" x 100'	0 34481 23301 5	100	22" x 22" x 6"	11.68	1.68
15005-025	1/2" x 25'	0 34481 04418 5	25	15" x 15" x 3.5"	3.61	0.45
15005-100	1/2" x 100'	0 34481 23305 3	100	22" x 22" x 6"	12.66	1.68
15007-025	3/4" x 25'	0 34481 04421 5	25	15" x 15" x 3.5"	3.61	0.45
15007-100	3/4" x 100'	0 34481 23315 2	100	22" x 22" x 6"	18.08	1.68
15008-100	1" x 100'	0 34481 23328 2	100	24" x 24" x 8"	27.80	2.67
15009-100	1-1/4" x 100'	0 34481 23335 0	100	30" x 30" x 9"	37.80	4.69
15010-100	1-1/2" x 100'	0 34481 23341 1	100	30" x 30" x 9"	46.50	4.69
15011-050	2" x 50'	0 34481 23348 0	50	30" x 30" x 9"	32.96	4.69

Carflex® Kits



Part #	Product Size	UPC Code	Carton Quantity	Carton Dimensions (L x W x H)	Case Weight (Lbs)	Case Cube (Cu. Ft.)
150DRB	1/2" x 6'	0 34481 04218 1	6	24" x 16" x 15"	15.57	3.33
150ERB	3/4" x 6'	0 34481 04219 8	6	24" x 16" x 15"	18.97	3.33
150FRB	1" x 6'	0 34481 16138 7	4	16" x 12" x 12"	9.79	3.33

Carlon® Carflex® Conduit and Fittings provide protection for outdoor electrical applications. Perfect for installation and repair of air conditioners, heat pumps, jacuzzis, swimming pool pump motors, and other outdoor applications.

Carflex® Pre-Wired Liquidtight Whips



Part #	Product Size	UPC Code	Carton Quantity	Carton Dimensions (L x W x H)	Case Weight (Lbs)	Case Cube (Cu. Ft.)
WCD6	1/2" x 6', #10 wire	0 34481 12822 9	6	16" x 12" x 11.5"	14.28	1.28
WCE6	3/4" x 6', #8 wire	0 34481 12805 2	6	16" x 12" x 11.5"	14.28	1.28

Carflex® Liquidtight Whip assemblies save the customer time and hassle of having to hunt for the needed components. Our moisture tight, nonmetallic, flexible conduit system is ideal for installing swimming pool motors, hot tub spas, air conditioners, pumps, outdoor lighting and more.

Unlike plastic coated metal conduit, the Carlon® Carflex System has no metal core to fatigue, rust, or corrode. The Carflex System has no sharp edges or burrs to cut into the wire insulation. Metal conduit is subject to fatigue and penetration of moisture.

The Carflex Liquidtight Whip assembly is complete with Carflex moisture tight conduit, wire, one straight fitting, and one 90° fitting.

All this makes for quick and trouble free installation.

