

Amazing GOOP®

Unique Family of Products

Strongest Adhesives & Epoxies Available

Ready-To-Use Spackling

Strong Brand Name

The **Amazing GOOP®** family of adhesives and epoxies continues to grow! Innovation drives us to create the strongest adhesives available and continues to introduce a variety of different epoxies for home and industrial use. We've added unique, problem-solving products such as two-part epoxy pastes, aerosol epoxies with grit, epoxy coatings and Nail Hole Filler spackling with a unique applicator tip. This wide range of options provides retailers with a quality family of products that customers have known and asked for – for almost 40 years!



ADHESIVES

Adhesives - Self Leveling



The Strongest, Most Flexible All Purpose Adhesives Ever Created.

GLUES WHATEVER. BONDS FOREVER!®

Amazing GOOP® DOUBLE AND TRIPLE THE STRENGTH Independent Laboratory Tests Prove it!

	Amazing GOOP	GORILLA	Heavy Duty Adhesive All-Purpose WELDER
Wood	53	15	33
Laminate (counter top) Raw-Side	61	25	30
Laminate (counter top) Gel-Side	47	24	22
Fiberglass Composite (Gel Coat Side)	66	27	30
Ceramic	38	25	29
Glass	79	29	27
Tile	37	28	32
Steel	74	25	31
Copper	43	20	27
Aluminum	64	23	26
Brass	73	31	22
ABS	36	19	25

Adhesive Strength Comparison Testing Results 180° peel strength test according - AS

Individual Size	Sales Part	Item UPC	Case Barcode	Case Pack	Case Weight	Case Dimensions (H x W x D in inches)	Case Cube	
Plumbing	3.7 fl oz	150011	0 76818-15001 5	1 00 76818-15001 2	6	2.10 lbs	9.13 x 5.88 x 6.25	0.19 ft³
	3.7 fl oz	150012	0 76818-15001 5	2 00 76818-15001 9	12	3.95 lbs	9.00 x 6.00 x 10.75	0.34 ft³
Automotive	3.7 fl oz	160011	0 76818-16001 4	1 00 76818-16001 1	6	2.10 lbs	9.13 x 5.88 x 6.25	0.19 ft³
	3.7 fl oz	160012	0 76818-16001 4	2 00 76818-16001 8	12	3.95 lbs	9.00 x 6.00 x 10.75	0.34 ft³
Craft	2.0 fl oz	190511	0 76818-90511 0	1 00 76818-90511 7	6	1.45 lbs	7.50 x 3.75 x 8.25	0.13 ft³
	2.0 fl oz	190512	0 76818-90511 0	2 00 76818-90512 1	12	2.35 lbs	7.50 x 5.00 x 8.50	0.18 ft³
Wood & Furniture	3.7 fl oz	180011	0 76818-18001 2	1 00 76818-18001 9	6	2.10 lbs	9.13 x 5.88 x 6.25	0.19 ft³
	3.7 fl oz	180012	0 76818-18001 2	2 00 76818-18001 6	12	3.95 lbs	9.00 x 6.00 x 10.75	0.34 ft³
Household	3.7 fl oz	130011	0 76818-03001 0	1 00 76818-03001 7	6	2.10 lbs	9.13 x 5.88 x 6.25	0.19 ft³
	3.7 fl oz	130012	0 76818-03001 0	2 00 76818-03001 4	12	3.95 lbs	9.00 x 6.00 x 10.75	0.34 ft³
Amazing	1.0 fl oz	140031	0 76818-14021 4	8 00 76818-14021 0	6	0.70 lbs	4.13 x 4.31 x 8.13	0.08 ft³
	1.0 fl oz	140032	0 76818-14021 4	2 00 76818-14021 8	12	1.35 lbs	8.50 x 4.75 x 7.88	0.18 ft³
Amazing Multi-Pack	0.18 fl oz	5510100	0 76818-10100 0	2 00 76818-10100 4	12	1.30 lbs	7.75 x 3.88 x 8.50	0.15 ft³

ADHESIVES

Bonds to practically anything
Fixes practically everything
Clear, flexible & waterproof
Won't crack or break like super glue

Adhesives - UV Resistant

STRENGTH OF OTHER LEADING ADHESIVES

LIQUID NAILS	White Glue	THE ORIGINAL SUPER GLUE
7	32	28
6	31	22
6	9	32
9	19	33
12	22	29
7	19	33
9	20	29
10	38	20
8	18	38
9	18	29
9	22	25
8	13	31

ASTM D 903 Average Max. Load Measured in PSI (lbs per square inch)



Point-of-purchase substrates demonstrate strength & versatility



Individual Size	Sales Part	Item UPC	Case Barcode	Case Pack	Case Weight	Case Dimensions (H x W x D in inches)	Case Cube	
Lawn & Garden	3.7 fl oz	210011	0 76818-21001 6	1 00 76818-21001 3	6	2.05 lbs	9.13 x 5.88 x 6.25	0.19 ft ³
	3.7 fl oz	210012	0 76818-21001 6	2 00 76818-21001 0	12	3.95 lbs	9.00 x 6.00 x 10.75	0.34 ft ³
Sport & Outdoor	3.7 fl oz	120011	0 76818-02001 1	1 00 76818-02001 8	6	2.15 lbs	9.13 x 5.88 x 6.25	0.19 ft ³
	3.7 fl oz	120012	0 76818-02001 1	2 00 76818-02001 5	12	4.10 lbs	9.00 x 6.00 x 10.75	0.34 ft ³
RV	3.7 fl oz	165012	0 76818-65012 6	2 00 76818-65012 0	6	3.85 lbs	9.00 x 6.00 x 10.75	0.34 ft ³
Marine	3.7 fl oz	170011	0 76818-17001 3	1 00 76818-17001 0	6	2.05 lbs	9.13 x 5.88 x 6.25	0.19 ft ³
	3.7 fl oz	170012	0 76818-17001 3	2 00 76818-17001 7	12	3.95 lbs	9.00 x 6.00 x 10.75	0.34 ft ³
	10.2 fl oz	172012	0 76818-17201 7	2 0076818-17201 1	12	9.95 lbs	11.75 x 6.00 x 8.12	0.33 ft ³

ADHESIVES

Shoe Repair & Protective Coating



The Original Shoe Goo® has been the consumer's choice for rebuilding, repairing and protecting shoes for almost 40 years!

Rebuild your worn-out soles overnight

Seal rubber & work boots, galoshes and waders

Coat and protect shoes and gloves to avoid premature wear

Reattach damaged heels and secure loose insoles

Reinforce skate shoes

Waterproof & seal boot seams



Individual Size	Sales Part	Item UPC	Case Barcode	Case Pack	Case Weight	Case Dimensions (H x W x D in inches)	Case Cube
Shoe Goo							
Clear							
1.0 fl oz	110131	0 76818-01021 0	1 00 76818-01021 7	6	0.80 lbs	4.13 x 5.13 x 8.25	0.10 ft ³
1.0 fl oz	110132	0 76818-01021 0	2 00 76818-01021 4	12	1.40 lbs	8.50 x 4.75 x 7.50	0.18 ft ³
3.7 fl oz	110011	0 76818-01001 2	1 00 76818-01001 9	6	2.05 lbs	9.13 x 5.88 x 6.25	0.19 ft ³
3.7 fl oz	110012	0 76818-01001 2	2 00 76818-01001 6	12	3.85 lbs	9.00 x 6.00 x 10.75	0.34 ft ³
0.18 fl oz (500 per box)	110400	0 76818-10436 0	8 00 76818 10436 6	1	10.70 lbs.	4.50 x 10.50 x 13.50	0.37 ft ³
Black							
3.7 fl oz	110212	0 76818-10212 0	2 0076818-10212 4	12	3.95 lbs	9.00 x 6.00 x 10.75	0.34 ft ³
Boots & Gloves							
Clear							
2.0 fl oz	110610	0 76818-10611 1	1 00 76818-10611 8	6	1.45 lbs	7.50 x 3.75 x 8.25	0.13 ft ³

SPACKLE

Nail Hole Filler

Amazing GOOP® Nail Hole Filler is a ready-to-use spackling requiring NO mixing, NO messy putty knives and NO scraping or sanding!

Dries in 15 minutes

Unique applicator

No touchup required



Fill & Texture



Paint



Finished



Clip Strip



Display

Individual Size	Sales Part	Item UPC	Case Barcode	Case Pack	Case Weight	Case Dimensions (H x W x D in inches)	Case Cube
Display — net wt. 8.2 oz	310015	0 76818-10015 7	2 00 76818-10015 1	12	7.46 lbs	6.75 x 8.70 x 9.50	0.32 ft ³
Clip Strip — net wt. 8.2 oz	310011	0 76818-10015 7	1 00 76818-10015 4	12	7.55 lbs	3.25 x 9.00 x 14.50	0.25 ft ³
Case — net wt. 8.2 oz	310010	0 76818-10015 7	1 00 76818-10010 9	6	3.90 lbs	3.25 x 9.00 x 14.50	0.25 ft ³

EPOXIES

Epoxy Paste



Point-of-purchase



Amazing GOOP® Epoxies are often stronger than the material being repaired and are resistant to chemicals, fuel, motor oils, transmission and hydraulic fluids, anti-freeze, alcohol, water and grease.

Formulated to mold into any shape




Great for overhead and vertical applications/Non-sag

Work under water

Permanent bond to most any surface

Sand it, paint it, drill it, plane it

CHOOSE THE RIGHT EPOXY FOR THE JOB

	DESCRIPTION	COLOR	USES	BENEFITS	APPLY TO	SET/WORKING TIME	CURE TIME	STRENGTH	HEAT RESISTANCE
SUPERMEND® EPOXY PASTE 	versatile all purpose high density	off-white ①	kitchen appliances shelves & cabinets plastic toys, furniture sports equipment porcelain & china	drill & tap no shrinkage non-sag waterproof	fiberglass, PVC, metal, fiberglass, most plastics, wood, Styrofoam™, aluminum ②	15 minutes @ 70 °F/21 °C	4 hours ③ @ 70 °F/21 °C	compress 36,000 psi tensile 7,450 psi shear 2,700 psi bond 1,750 psi	140 - 150 °F 60 - 66 °C ④
MARINE EPOXY PASTE 	extra fast bonding high density	light beige ①	keels & skegs hulls & decks pools & spas boat blister pox seal leaks	cures in temperatures to 34 °F/1 °C non-sag sands like real wood	fiberglass, wood, steel, ABS, PVC, CPVC, copper, most plastics ②	5 minutes @ 70 °F/21 °C	20 minutes ③ @ 70 °F/21 °C	compress 36,000 psi tensile 7,450 psi shear 2,700 psi bond 1,700 psi	190 °F 88 °C ④
AUTOMOTIVE EPOXY PASTE 	high temperature metalized medium density	primer gray ①	cold welding repairs radiator seams engine blocks metal caps & gas lines garden & metal tools auto bodies & bikes	high heat resistance drill & tap non-sag chemical resistant	steel, iron, copper, aluminum, bronze, metal castings, most plastics, graphite, fiberglass ②	20 minutes @ 70 °F/21 °C	2.5 hours ③ @ 70 °F/21 °C	compress 36,000 psi tensile 7,450 psi shear 2,700 psi bond 1,850 psi	250 °F 121 °C ④

- ① To match epoxy to surface, epoxy may be tinted with powder colorants, most water-based colorants and food dye.
- ② Epoxy Pastes bond to all surfaces except polypropylene, teflon, and polyethylene. All surfaces should be roughened prior to application.
- ③ Cure times are based on an application thickness of 1/8". Cure time is the amount of time required before sanding or painting.
- ④ Heat resistance values are based on intermittent temperatures. Product may soften when exposed to constant higher temperatures.

Individual Size	Sales Part	Item UPC	Case Barcode	Case Pack	Case Weight	Case Dimensions (H x W x D in inches)	Case Cube	
SuperMend	4.0 oz	5330031	0 14804-73000 1	5 00 14804-73000 6	8	4.80 lbs	6.75 x 4.75 x 8.50	0.16 ft³
	16.0 oz	5330061	0 14804-74000 0	2 00 14804-74000 4	6	12.45 lbs	8.50 x 6.88 x 9.50	0.32 ft³
Marine	4.0 oz	5300031	0 14804-60740 2	5 00 14804-60740 7	8	4.55 lbs	6.75 x 4.63 x 8.75	0.16 ft³
Automotive	4.0 oz	5350031	0 14804-83000 8	5 00 14804-83000 3	8	4.65 lbs	6.50 x 4.63 x 8.88	0.16 ft³

EPOXIES

Coatings & Aerosol

Amazing GOOP® COAT-IT® is a graphite black epoxy that is 100% solids and waterproof. Provides an armor type coating for the bottom of fishing boats, kayaks and canoes. It creates slip and lubricity when boats come into contact with rocks, gravel or shrubs while protecting the boat from damage.

Provides superior scratch resistance

Reinforced with Kevlar®

Fast curing

Use above and below the waterline



Amazing GOOP® Anti-Skid Epoxy provides a hard, flat, textured finish that helps avoid slip and fall accidents in a convenient aerosol can. It is friendly on bare feet, lead-free, chemical, gas and oil resistant and can be used indoors or outdoors. It is ideal for areas where water is present or slippery conditions exist and can be used on properly prepared wood, concrete, metal, fiberglass, tiles, porcelain and many more.

Easy to use & dries quickly

Maximum durability

Strong adhesion



Eye catching merchandiser allows point-of-purchase information



CHARACTERISTICS

Abrasion resistance	Very high
Lubricity	Exhibits high lubricity in marine applications.
Waterproof	Yes, unique epoxy sealer.
Heat deflection temperature	116 °F / 47 °C (ASTM D648-264 psi)
Bond strength	2,020 psi (mild steel to mild steel)

CHARACTERISTICS

Substrates	Wood, concrete, metal, fiberglass, tiles, porcelain and many more.
Color	Clear or white; black, gray, & safety colors available with minimum batch sizes.*
Grit	No sharp edges and friendly on bare feet.
Coverage	Up to 15 sq. ft. per can.
Dry to Touch	Dries quickly in 10 to 20 minutes at 77 °F / 25 °C

*Special colors such as Gray, Safety Yellow and Safety Orange also available with minimum order quantities.

Individual Size	Sales Part	Item UPC	Case Barcode	Case Pack	Case Weight	Case Dimensions (H x W x D in inches)	Case Cube
COAT-IT	2.0 lb Kit	540040	0 14804-90000 8	2	5.05 lbs	10.75 x 4.75 x 8.75	0.26 ft³
	8.0 lb Kit	540060	0 14804-90200 2	2	19.95 lbs	12.00 x 7.75 x 14.00	0.75 ft³
Anti-Skid Epoxy All-Purpose	11 oz - Clear	5370020	0 76818-70020 3	6	6.25 lbs.	8.50 x 5.75 x 8.38	0.24 ft³
	11 oz - White	5370021	0 76818-70021 0	6	6.25 lbs.	8.50 x 5.75 x 8.38	0.24 ft³
	11 oz - Black	5370022	0 76818-70022 7	6	6.25 lbs.	8.50 x 5.75 x 8.38	0.24 ft³
Bath, Tub & Tile	11 oz - Clear	5370120	0 76818-70120 0	6	6.25 lbs.	8.50 x 5.75 x 8.38	0.24 ft³



ECLECTIC
IN THE HOME & ON THE JOB PRODUCTS

Eclectic Products, Inc.
101 Dixie Mae Drive
Pineville LA 71360-3993
1 (800) 349-4667

For more information about individual products, please contact your sales representative or call (800) 349-4667. For additional literature and P.O.P. order forms, please call (800) 693-4667.